Table 3-23. Soil Types and Properties at the Klondike Flats Site

Soil Name	Taxonomy	Depth (inches)	рН	Salinity (mmho/cm)	Permeability (inches/hour)	Available Water (percent)	Textural Class	Clay (percent)	Erodibility Factors <sup>a</sup>
Chipeta	Clayey, mixed (calcareous), mesic, Typic Torriorthents	5–20	7.4–9.0	8–16	0.06–0.2	9–16	Clay to silty clay loam	30–45	K = 0.43 T = 1 Wind = 6
Ravola	Fine-silty, mixed (calcareous), mesic Typic Torrifluvents	> 60	7.9–9.0	4–16	0.2–6.0	10–18	Silt loam	15–35	K = 0.43 T = 5 Wind = 4
Toddler	Fine-silty, mixed (calcareous), mesic Typic Torrifluvents	> 60	7.9–9.0	2–8	0.6–2.0	10–18	Silt loam to fine sandy loam	18–35	K = 0.32 T = 5 Wind = 4
Glenton	Coarse-loamy, mixed (calcareous), mesic Typic Torrifluvents	> 60	7.9–8.4	< 8	2.0–6.0	8–18	Silt loam to fine sandy loam	5–18	K = 0.24 T = 5 Wind = 3
Nakai	Coarse-loamy, mixed, mesic Typic Calciorthids	40->60	7.4–8.4	< 2	2.0-6.0	10–16	Fine sandy loam to loamy fine sand	10–18	K = 0.28 T = 3 Wind = 3

<sup>&</sup>lt;sup>a</sup>Erodibility factors:

K, used in the Universal Soil Loss Equation, is an indicator of the susceptibility of a soil to sheet and rill erosion by water. Values range from 0.02 to 0.69; the higher the value, the more susceptible the soil is to sheet and rill erosion.

Remediation of the Moab Uranium Mill Tailings, Grand and San Juan Counties, Utah Final Environmental Impact Statement

T is an estimate of the maximum average annual rate of water or wind erosion in tons per acre per year.

Wind erosion factors range from 1 to 8; the lower the value, the more susceptible the soil is to wind erosion.

mmho/cm = millimhos per centimeter.

Source: SCS 1989.